

imagePROGRAF TA-20

COMPACT AND INTUITIVE DEVICE FOR HIGH PRINT QUALITY

A versatile and compact multi-purpose printer designed for schools, offices and retail with low volume print jobs.



- **High Print Quality**
Innovative imaging technology delivers precise printing, with powerful colour from LUCIA TD ink
- **Quiet and compact**
Seamlessly fits into any office, with reduced operation noise and full front accessibility
- **Accurate ink placement**
Print sharp lines with an innovative Air Feeding System that keeps paper flat for high accuracy
- **Strengthened security**
Security requirements and settings for secure communication, secure management and secure interface
- **Ease of use**
3" inch color LCD touchscreen panel with ample icons for immediate access

PRODUCT RANGE



imagePROGRAF TA-30



imagePROGRAF TA-20



imagePROGRAF TM-200

Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF TA-20

TECHNOLOGY

| | |
|----------------------------|---|
| Printer Type | 5 colors 24"/610mm |
| Print Technology | Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head) |
| Print Resolution | 2,400 x 1,200 dpi |
| Number of Nozzles | 15,360 nozzles (MBK 5,120 nozzles, Other Colors 2,560 nozzles each) |
| Line Accuracy | ±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only |
| Nozzle Pitch | 1,200dpi (2 lines) |
| Ink Droplet Size | minimum 5 pl per colour |
| Ink Capacity | Sales Ink: 55ml Bundled Starter Ink: 55ml (2 x MBK, 1 x BK,C,M,Y) |
| Ink Type | Pigment inks - Matte Black, Black, Cyan, Magenta, Yellow |
| OS Compatibility | Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10 Microsoft Windows 64 Bit: Windows 7, 8.1, 10, Windows Server 2008R2, Windows Server 2012/2012R2, Windows Server 2016, Windows Server 2019 Apple Macintosh: OS X 10.10.5-OS X 10.11, macOS 10.12- macOS 10.15 |
| Printer Languages | SG Raster (Swift Graphic Raster),HP-GL/2, HP RTL, JPEG (Ver. JFIF1.02) |
| Standard Interfaces | USB B Port: Hi-Speed Ethernet: IEEE 802.3 10base-T/IEEE 802.3u 100base-TX/IEEE 802.3ab 1000base-T/IEEE 802.3x Full Duplex Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b * Please refer to user manual how to activate/deactivate the wireless LAN |

MEMORY

| | |
|------------------------|------|
| Standard memory | 2 GB |
| Hard Drive | NO |

PRINT TIME FOR A1 PAGE SIZE

| | Print Mode | Print Time |
|---|-------------------|-------------------|
| CAD Drawing | Fast | 00:32 min |
| | Standard | 00:56 min |
| Poster | Fast | 00:30 min |
| | Standard | 00:49 min |
| Heavy Coated Paper (A1 paper size) | Fast | 00:58 min |
| | Standard | 01:46 min |

MEDIA HANDLING

| | |
|------------------------------------|--|
| Media Feed and Output | Roll Paper: One Roll, Upper-loading, Front Output Cut Sheet: Upper-loading, Front Output (Manual feed using media locking lever) |
| Media Width | Roll paper: 203.2 - 610 mm Cut sheet: 210 - 431.8 mm |
| Media Thickness | Roll/Cut: 0.07 - 0.8 mm |
| Minimum Printable Length | Roll paper: 203.2 mm Cut sheet: 279.4 mm |
| Maximum Printable Length | Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 594mm |
| Maximum Media Roll Diameter | 150 mm or less |
| Media Core Size | Internal diameter of roll core: 2"/3"(option) |
| Margins Recommended area | Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm |

Margins Printable area

Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm
Roll paper (borderless): Top: 20 mm, Bottom: 0 mm, Side: 0 mm
Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm
Manually switchable by user

Media Feed Capacity

Media Take-up roll unit
Borderless Printing Width (Roll Only)

N/A
(Printable) 203.2-610mm
*Roll paper only * No size restriction
Standard position: 1 sheet

Maximum number of delivered prints

DIMENSIONS AND WEIGHT

Physical Dimensions WxDxH (mm) and Weight (Kg)

982 x 748 x 438 mm
37 kg (including Roll Holder Set, excluding ink and print head)

Packaged Dimensions WxDxH (mm) and Weight (Kg)

Printer (Main unit with pallet) 1147 x 874 x 542 mm
49 kg

POWER AND OPERATING REQUIREMENTS

Power Supply

AC 100-240V (50-60Hz)

Power Consumption

Operation: 52 W or less
Sleep mode: 3.6W or less
Default setting for the time to enter the Sleep mode: approx. 5 mins
Power off: 0.3 W or less

Operating Environment

Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)

Acoustic Noise (Power/Pressure)

Operation: 42 dB (A) (Plain paper, line drawing, standard mode)
Standby: 35 dB (A) or less
Operation: 5.8 Bels (Plain paper, line drawing, standard mode) (Measured on ISO 7779 standard and described based on ISO9296 standard)

Regulations

Europe: CE mark, Russia: EAC,

Certificates

TUV, CB

WHAT'S INCLUDED

What's in the Box?

Printer, 1 print head, Power Cabel, 1 set of starter ink tanks, Set up guide, Quick Guide, Safety/Standard Environment leaflet, User Software CD-ROM (Win), EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet

Software Included

imagePROGRAF TA- Unified Printer Driver, Other software available as Download from Web.

OPTIONS

Optional Items

2/3" Roll Holder: RH2-28

CONSUMABLES

User Replaceable Items

Ink Tank: PFI-030 (55ml)
Print Head: PF-06
Cutter Blade: CT-08
Maintenance Cartridge: MC-31

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice,™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2019