

MP C401SP MP C401SRSP MP C401ZSP MP C401ZSRSP



☑ Copy ☑ Print ☑ Scan ☑ Fax



Compact A4 colour MFPs to increase your productivity

Top performance, outstanding reliability, high productivity ... and exceptional value for money. That's what you get with the MP C401SP/MP C401SRSP/MP C401ZSP/MP C401ZSRSP, Ricoh's compact A4 colour multifunctionals. But that's not all. You also get consistently high quality results, superior image quality and efficient finishing capabilities. Plus simple, intuitive operation, a low environmental impact, and a choice of four configurations. The MP C401SP/MP C401SRSP/MP C401ZSP/MP C401ZSP/MP C401ZSRSP are therefore the obvious choice for offices where productivity, workflow, quality and cost-efficiency are high on the priority list.

RICOM

- Time-saving: fast printing at 40 cpm
- Affordable: reduction of total costs
- Easy to use: large operating panel
- · Highly versatile: compact internal finisher
- Long-lasting: long duty cycle

MP C400w

Unmatched performance with unrivalled ease of use

Highly productive and durable

The incredible speed and performance of the MP C401SP/MP C401SRSP/MP C401ZSP/MP C401ZSRSP mean that you no longer have to wait for your printouts. After warming up, the first B/W print is available only 5.4 seconds later (colour in 7.2 seconds). These devices then zoom along at a busy 40 pages per minute. They are also exceptionally durable, built to withstand a long lifetime of heavy-duty use. Typical lifecycles are high, and the ARDF is solidly built for high reliability.

Advanced functionality to improve your workflow

Save time looking for documents by using the Searchable PDF function (with optional OCR only). You can even search for a document via a single word that appears in the text. Save paper and time by copying both sides of an ID card onto one side of paper with ID Card Copy. Utilise XPS media print to print documents based on Microsoft's new XML format directly from a USB slot or PC – without a driver.

Environmentally responsible

Overall energy consumption of the MP C401SP/MP C401SRSP/MP C401ZSP/MP C401ZSRSP is as low as possible to reduce environmental impact and your energy costs. Machines can spend up to 50% of their life in sleep mode, so power consumption during sleep mode has been cut to an all-time low. The power on/off setting further optimises electricity consumption. These MFPs print in duplex mode by default to save paper – animated indicators on the operating panel show you how much paper you are saving.



Easy to operate

Choose the type of operating panel you feel most comfortable with. The conventional large 9-inch display is familiar and easy to use. But why not try out the latest Ricoh touch and swipe panel? Its operation is similar to iPad and Android devices, enabling you to manage complex jobs quickly and smoothly. Another feature to improve usability is external USB keyboard support which enables easier and smoother typing.



MP C401SP/MP C401SRSP/MP C401ZSP/MP C401ZSRSP

MAIN SPECIFICATIONS

GENERAL

Warm-up time: First output speed:

Continuous output speed: Memory: HDD:

PJ WX2440: x pixels (WXGA) PJ X2440: x pixels (XGA) PJ S2440: x pixels (SVGA) Dimensions (W x D x H): Weight: Power source:

B/W: 5.4 seconds 40 pages per minute Standard: 2 GB

220 - 240 V, 50/60 Hz

46/46/55/55 seconds

Full colour: 7.2 seconds

COPIER

Copying process: Dry electrostatic transfer system Multiple copying: Up to 999 copies Resolution 600 x 600 dpi From 25% to 400% in 1% steps Zoom:

PRINTER

Printer language:	Standard: PCL5c, PCL6, Adobe® PostScript® 3™, Mediaprint (JPEG/TIFF) Option: XPS
Print resolution:	1,200 x 1,200 dpi
Interface:	Standard: USB 2.0, SD slot, USB Host I/F, Ethernet 10 base-T/100 base-TX, Gigabit Ethernet Option: Wireless LAN (IEEE 802.11a/b/g/n), Bluetooth
Network protocol:	TCP/IP (IP v4, IP v6), Bonjour
Windows® environments:	Windows® 7, Windows® 8, Windows® Server 2003, Windows® Server 2008, Windows® Server 2008R2, Windows® Server 2012
Mac OS environments:	Macintosh OS X Native v10.6 or later
UNIX environments:	UNIX Sun® Solaris: 2.9, 2.10 HP-UX: 11.x, 11i v2, 11i v3 SCO OpenServer: 5.0.6, 5.0.7, 6.0 RedHat® Linux Enterprise: 4, 5, 6 IBM® AIX: 5L v5.3, 5L v6.1, 5L v7.1
Novell® Netware® environments	v6.5 or later (option)
SAP® R/3® environments:	SAP® R/3 3.x® or later, mySAP ERP 2004 or later

Maximum 30 originals per minute

E-mail, Folder, USB, SD card

Maximum: 600 dpi

Network TWAIN

Α4

SCANNER

Scanning speed: Resolution: Original size Bundled drivers: Scan to:

320 GB (Encryption/Data Overwrite Security unit) 578 x 574 x 710 mm 80/85/80/85 kg

FAX (option)

Circuit:

Compatibility:
Resolution:
Transmission speed:
Modem speed:
Scanning speed:
Memory capacity:

PSTN ITU-T (CCITT) G3, PSTN 8 x 3.85 line/mm, 100 x 200 dpi 8 x 7.7 line/mm, 200 x 200 dpi G3: 2 second(s) Maximum: 33.6 Kbps 2 second(s) Standard: 4 MB Maximum: 28 MB

PAPER HANDLING

Recommended paper size:	
Paper input capacity:	

Paper output capacity:

Standard paper tray(s): A4, A5, A6, B5, B6 Bypass tray: A4, A5, A6, B5, B6 Maximum: 2,300 sheets Maximum: 650 sheets Paper tray(s): 52 - 220 g/m² Bypass tray: 52 - 256 g/m²

ECOLOGY

Paper weight:

Power consumption:

Maximum: 1,570 W Ready mode: 202 W Low power mode: 106 W Sleep mode: Less than 0.91 W TEC (Typical Electricity Consumption): 3.876 Wh

SOFTWARE

Standard:

Optional:

SmartDeviceMonitor, Web SmartDeviceMonitor®, Web Image Monitor
GlobalScan NX, Card Authentication Package, Unicode Font Package for SAP, Remote Communication Gate S Pro

OPTIONS

1 x 550-sheet paper tray, 2 x 550-sheet paper tray, One-bin tray, Side tray, Low cabinet, High cabinet, Wireless LAN (IEEE 802.11a/b/g/n), Bluetooth, Netware, Pictbridge, Browser unit, Counter interface, File format converter, Data Overwrite Security Unit (Certified version), Copy Data Security Unit, Fax Connection Unit, Fax memory (32 MB), Fax option, OCR Unit

CONSUMABLES

Toner capacity:

Black: 10,000 prints Cvan: 10.000 prints Magenta: 10,000 prints Yellow: 10,000 prints

Consumable yield figures are based on 2 p/j 5% coverage on A4

For availability of models, options and software, please consult your local supplier.

ISO9001 certified ISO14001 certified. ISO27001 certified

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2018 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.

RICOH imagine. change.

www.ricoh-europe.com